



Technical Review
MaxR300™
 Diesel Fuel Enhancer

www.lubesolv.com
 info@lubesolv.com

MaxR300™ Diesel Fuel Conditioner is designed to protect equipment by combating the harmful effects of today's fuels while improving performance and increasing the useful life of any diesel engine. It is green in color and is compounded from pure petroleum products and their derivatives.

MaxR300™ is for diesel engine only, and will increase the cetane rating of any diesel fuel it is added to as well as lower gel points. It reduces acid formation and lubricates the entire fuel system. This product will keep a new engine clean or clean a high mileage engine. **MaxR300™** keeps injectors spotless for easier starts, improved power and better mileage while it absorbs any condensation moisture in the fuel tank. It lubricates fuel pumps for longer life. For lower maintenance costs and longer engine life use **MaxR300™** in every tankful. **MaxR300™** is equally beneficial and most convenient when added to fuel storage tanks.

MaxR300™ Core Benefits	
Reduce Engine Acid Formation	Lower Diesel Fuel Gel Point
Provide More Complete Combustion	Absorb Moisture Condensation
Keep Injectors Clean	Provide Very Effective Top Cylinder Lubrication
Reduce Fuel Consumption	Reduce Smoke Emissions
Allow Easier Starting	Reduce Gum and Varnish Buildup
Provide Higher Cetane Rating	Eliminate Ring Sticking
Clean up a Dirty Engine	Reduce Maintenance Costs

General Applications

MaxR300™ can be safely added to any diesel fuel. The use **MaxR300™** whenever storing diesel equipment (or fuel in tanks) for extended intervals will provide excellent lubrication while protecting against fuel deterioration and the effects of condensation moisture on all metal parts.

Directions for Use

In Fuel Storage Tanks - 1 gallon **MaxR300™** to every 200 gallons diesel fuel.

Vehicle Fuel Tanks – 1 oz. **MaxR300™** to diesel fuel tank for each 1.5 gallons of fuel. Pour in prior to filling vehicle tank. Filling tank will mix **MaxR300™** and fuel adequately.

Long Term Storage of Equipment or Fuel in Tanks: 1 gallon **MaxR300™** per 100 gallons fuel. After storage period (up to 2 yrs), use fuel in normal way, then return to 1 gallon for every 200 gallons fuel.



Associative Products

The manufacturer of **MaxR300™** also makes **MaxR100™** for air conditioning & refrigeration systems.

ColdAir™ is formulated for automotive refrigerant. **MaxR200™** is a general purpose anti-friction compound that can be added to engines, transmissions, differentials, power steering, hydraulic systems, grease, generators, pumps, transformers, or used straight up as a cutting fluid. Extended a/c life is also a benefit of using this unique technology. Also available is **MaxR300-G™** gas conditioner, which provides substantial fuel savings among many other benefits.



for more information please visit our website at www.lubesolv.com

Contact Name: _____	Fax #: _____
Contact Email: _____	Phone: _____